



SystemSafe Heat Transfer Fluid

Product Code : BHT001 / BHT002

Introducing a high-performance, non-toxic concentrated heat transfer fluid specifically designed for use in Air and Ground Source Heat Pumps and underfloor heating systems.

This product offers superior protection against corrosion and limescale, while providing frost protection ranging from -4°C to -32°C. This heat transfer fluid also carries a biocide to protect against microbial growth.

Its compatibility with all materials commonly found in Heat Pump and underfloor heating systems, along with its pH stability, makes it the ideal choice for ensuring the longevity and efficiency of your heating systems.

Product Features

- Non-toxic concentrated heat transfer fluid suitable for both air & ground source heat pumps, plus solar and UFH systems.
- Contains both Corrosion & Scale Inhibitor plus a Biocide protection to protect against microbial growth. NSF CIAS certified.
- Provides a wider operating temperature range than water alone, together with excellent heat transfer properties across the extended temperature range.
- Suitable for use with steel, stainless steel, brass, copper, aluminium and all plastics commonly used in heating system construction.

Product Specification

Concentration : 10, 20, 25, 33, 40, 50%

Protection : -4, -9, -11, -16, -22, -32°C

PH (Conc) : 8.2 (7.5-8.5)

Form : Clear, colourless, yellow liquid

Odour : mild, aromatic

Maximum Temperature : 150°C

EAN / Barcode : 10L - 506013459 1725 - BHT001

EAN / Barcode : 20L - 506013459 1732 - BHT002

'high performance heat transfer fluid for a ASHP'

When you choose Kamco chemicals, you're selecting a trusted manufacturer with over 40 years of expertise in delivering effective solutions for power flushing and descaling across diverse global markets. Experience matters, and with Kamco, you're in good hands.



+44 1727 875020



info@kamco.co.uk



www.kamco.co.uk